

Liberty Gold - Black Pine Drill Holes

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	Comments	g/t x m
LBP800 (170, -75)	56.4	62.5	6.1	0.18	0.15 1.00 0.15	324.6	Rangefront Infill		41.9
and	77.7	83.8	6.1	0.17					
and	99.1	117.3	18.3	0.38					
and	128.0	140.2	12.2	0.34					
and	152.4	157.0	4.6	0.26					
and	170.7	179.8	9.1	0.35					
and	189.0	214.9	25.9	0.86					
including	190.5	192.0	1.5	1.28					
including	199.6	205.7	6.1	2.26					
and	249.9	254.5	4.6	0.41					
LBP801 (70, -45)	99.1	108.2	9.1	0.67	0.15 1.00	213.4	Back Range	Reduced AuCN below 129 m	15.8
including	102.1	103.6	1.5	1.35					
and	129.5	135.6	6.1	0.41					
and	141.7	144.8	3.0	0.39					
and	178.3	190.5	12.2	0.49					
including	178.3	181.4	3.0	1.18					
LBP807 (200, -80)	42.7	50.3	7.6	0.34	0.15 1.00 0.15	213.4	Rangefront Infill	30.5	
and	71.6	79.2	7.6	0.27					
and	80.8	85.3	4.6	0.31					
and	93.0	108.2	15.2	0.35					
and	115.8	135.6	19.8	0.32					
and	153.9	175.3	21.3	0.46					
including	161.5	163.1	1.5	1.06					
and	184.4	189.0	4.6	0.24					
and	196.6	202.7	6.1	0.28					
LBP816 (195, -55)	48.8	67.1	18.3	0.28	0.15 1.00 0.15 1.00	214.9	Rangefront Infill	29.0	
and	77.7	94.5	16.8	0.31					
and	115.8	120.4	4.6	0.35					
and	141.7	169.2	27.4	0.39					
including	141.7	143.3	1.5	1.05					
and	185.9	196.6	10.7	0.59					
including	187.5	189.0	1.5	1.72					
LBP818 (35, -70)	9.1	24.4	15.2	0.42	0.15 1.00	251.5	RF Infill	39.5	
and	68.6	74.7	6.1	0.28					
and	117.3	129.5	12.2	0.18					
and	131.1	140.2	9.1	0.24					
and	160.0	173.7	13.7	0.24					
and	175.3	187.5	12.2	0.17					
and	202.7	251.5	48.8	0.44					
including	246.9	248.4	1.5	1.54					
LBP821 (270, -65)	70.1	76.2	6.1	0.38	0.15	184.4	M Zone	Reduced AuCN	15.7
and	79.2	88.4	9.1	0.26					
and	100.6	114.3	13.7	0.55					
and	135.6	149.4	13.7	0.25					
LBP824 (280, -60)	100.6	105.2	4.6	0.23		233.2	RF Infill		14.4
and	131.1	161.5	30.5	0.33					
and	175.3	179.8	4.6	0.36					
and	204.2	208.8	4.6	0.34					
LBP825 (0, -90)	13.7	38.1	24.4	0.31	0.15 1.00 0.15	239.3	RF Infill		22.0
and	89.9	96.0	6.1	0.35					
and	140.2	169.2	29.0	0.38					
including	158.5	160.0	1.5	1.28					
including	163.1	164.6	1.5	1.47					
and	175.3	179.8	4.6	0.27					

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	Comments	g/t x m	
LBP826 (90, -65)	65.5	70.1	4.6	0.24	0.15	251.5	RF Infill		36.8	
and	85.3	102.1	16.8	0.28						
and	109.7	153.9	44.2	0.25						
and	169.2	175.3	6.1	0.19						
and	181.4	225.6	44.2	0.39						
including	199.6	202.7	3.0	1.44						1.00
and	237.7	243.8	6.1	0.28						0.15
LBP827 (150, -75)	79.2	85.3	6.1	0.36	0.15	205.7	M Zone	Redusced AuCN below 132 m	40.4	
and	96.0	109.7	13.7	0.56						
including	96.0	99.1	3.0	1.33	1.00					
and	117.3	120.4	3.0	0.38	0.15					
and	132.6	144.8	12.2	2.11						
including	132.6	141.7	9.1	2.61	1.00					
and	150.9	153.9	3.0	1.23	0.15					
including	152.4	153.9	1.5	2.09	1.00					
TW2 (0, -90)	No Significant Results					379.5	Neil Field Test Well #2			
LBP828 (0, -90)	No Significant Results					499.9	Section 36			
LBP829 (270, -70)	70.1	74.7	4.6	0.36	0.15	251.5	RF Infill		20.9	
and	80.8	86.9	6.1	0.36						
and	102.1	112.8	10.7	0.25						
and	114.3	123.4	9.1	0.20						
and	125.0	135.6	10.7	0.18						
and	141.7	178.3	36.6	0.22						
and	217.9	222.5	4.6	0.23						
and	228.6	233.2	4.6	0.32						
LBP830 (350, -75)	93.0	97.5	4.6	0.23	0.15	251.5	RF Infill		11.9	
and	123.4	150.9	27.4	0.22						
and	160.0	173.7	13.7	0.35						
LBP831 (0, -90)	385.6	393.2	7.6	0.25	0.15	426.7	NOI Site		1.9	
LBP832 (220, -75)	234.7	251.5	16.8	0.22	0.15	251.5	Gtech-003		3.6	
LBP833 (115, -60)	74.7	79.2	4.6	0.25	0.15	269.7	RF Infill		33.7	
and	96.0	97.5	1.5	0.95						
and	105.2	121.9	16.8	0.24						
and	146.3	164.6	18.3	0.25						
and	205.7	259.1	53.3	0.42						
including	248.4	249.9	1.5	1.10						1.00
LBP834 (280, -65)	4.6	7.6	3.0	0.34	0.15	202.7	M Zone		3.7	
and	12.2	16.8	4.6	0.27						
and	158.5	163.1	4.6	0.31						
LBP835 (70, -65)	125.0	144.8	19.8	0.26	0.15	257.6	RF Infill		24.5	
and	150.9	173.7	22.9	0.34						
and	189.0	221.0	32.0	0.33						
and	239.3	245.4	6.1	0.20						
LBP836 (350, -72)	38.1	39.6	1.5	0.85	0.15	221.0	RF Infill		32.6	
and	109.7	120.4	10.7	0.40						
and	134.1	167.6	33.5	0.39	1.00					
including	160.0	161.5	1.5	1.42						
and	181.4	216.4	35.1	0.40	0.15					
including	213.4	214.9	1.5	1.01	1.00					
LBP837 (100, -75)	No Significant Results					202.7	M Zone			

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	Comments	g/t x m
LBP838 (245, -45)	96.0	120.4	24.4	0.25	0.15	263.7	RF Infill		26.4
including	105.2	117.3	12.2	0.32	0.20				
and	121.9	132.6	10.7	0.22	0.15				
including	125.0	131.1	6.1	0.27	0.20				
and	144.8	150.9	6.1	0.23	0.15				
and	167.6	201.2	33.5	0.49	0.20				
including	189.0	190.5	1.5	1.05	1.00				
including	192.0	195.1	3.0	1.35					
LBP839 (170, -52)	97.5	120.4	22.9	0.17	0.15	251.5	RF Infill		43.6
and	146.3	249.9	103.6	0.38					
including	231.6	233.2	1.5	1.23	1.00				
including	242.3	245.4	3.0	1.34					
LBP840 (280, -55)	76.2	80.8	4.6	0.37	0.15	213.4	M Zone		1.7
LBP841 (210, -67)	153.9	185.9	32.0	0.33	0.15	233.2	RF Infill		15.9
and	192.0	205.7	13.7	0.39					
LBP842 (240, -47)	114.3	163.1	48.8	0.28	0.15	199.6	RF Infill		25.4
and	170.7	198.1	27.4	0.43					
LBP843 (235, -62)	No Significant Results					213.4	M Zone		
LBP844 (275, -50)	132.6	140.2	7.6	0.20	0.15	211.8	RF Infill		8.2
and	149.4	182.9	33.5	0.20					
LBP845 (305, -75)	77.7	102.1	24.4	0.40	0.15	330.7	RF Infill		33.7
including	97.5	99.1	1.5	1.05	1.00				
and	118.9	126.5	7.6	0.21	0.15				
and	150.9	195.1	44.2	0.25					
and	237.7	254.5	16.8	0.48					
and	266.7	272.8	6.1	0.54					
LBP846 (270, -80)	147.8	152.4	4.6	2.54	0.15	269.7	M Zone		15.1
including	149.4	152.4	3.0	3.67	1.00				
and including	149.4	150.9	1.5	5.14	5.00				
and	193.5	196.6	3.0	0.57	0.15				
and	251.5	254.5	3.0	0.56					
LBP847 (280, -60)	64.0	67.1	3.0	0.72	0.15	182.9	M Zone	Reduced AuCN below 79 m	16.5
including	65.5	67.1	1.5	1.13	1.00				
and	77.7	85.3	7.6	0.76	0.15				
including	77.7	79.2	1.5	1.02	1.00				
including	80.8	82.3	1.5	1.32					
and	152.4	166.1	13.7	0.62	0.15				
including	161.5	164.6	3.0	1.71	1.00				
LBP848 (100, -68)	93.0	112.8	19.8	0.35	0.15	324.6	RF Infill		15.6
and	153.9	178.3	24.4	0.22					
and	196.6	216.4	19.8	0.17					
LBP849 (230, -55)	12.2	16.8	4.6	1.08	0.15	178.3	M Zone	Reduced AuCN below 64 m	94.1
including	13.7	15.2	1.5	1.67	1.00				
and	30.5	35.1	4.6	0.24	0.15				
and	64.0	71.6	7.6	0.64					
including	64.0	65.5	1.5	1.71	1.00				
including	70.1	71.6	1.5	1.45					
and	115.8	118.9	3.0	1.31					
including	117.3	118.9	1.5	2.16	1.00				
and	128.0	135.6	7.6	0.77	0.15				
including	128.0	129.5	1.5	2.73	1.00				
and	152.4	178.3	25.9	2.83	0.15				
including	152.4	175.3	22.9	3.16	1.00				
and including	157.0	160.0	3.0	6.01	5.00				
and including	169.2	172.2	3.0	7.88					

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	Comments	g/t x m
LBP850 (190, -78)	80.8	91.4	10.7	0.34	0.15	349.0	RF Infill		19.9
and	181.4	216.4	35.1	0.36					
including	185.9	187.5	1.5	1.52	1.00				
and	228.6	234.7	6.1	0.33	0.15				
and	266.7	274.3	7.6	0.23					
LBP851 (185, -55)	No Significant Results					65.5	M Zone		
LBP852 (210, -60)	74.7	89.9	15.2	0.18	0.15	243.8	RF Infill		21.2
and	103.6	106.7	3.0	0.35					
and	117.3	141.7	24.4	0.33					
and	144.8	160.0	15.2	0.28					
and	161.5	179.8	18.3	0.27					
LBP853 (30, -75)	48.8	54.9	6.1	0.19	0.15	227.1	RF Infill		9.2
and	138.7	152.4	13.7	0.23					
and	153.9	166.1	12.2	0.29					
and	172.2	178.3	6.1	0.21					
LBP854 (330, -80)	33.5	39.6	6.1	0.41	0.15	208.8	RF Infill		11.3
and	93.0	102.1	9.1	0.17					
and	114.3	117.3	3.0	0.34					
and	123.4	150.9	27.4	0.23					
LBP855 (70, -50)	83.8	112.8	29.0	0.24	0.15	300.2	RF Infill		44.2
and	121.9	144.8	22.9	0.21					
and	181.4	193.5	12.2	0.35					
and	204.2	263.7	59.4	0.43	1.00				
including	237.7	240.8	3.0	1.65					
including	243.8	245.4	1.5	1.15					
including	246.9	248.4	1.5	1.10	0.15				
and	275.8	278.9	3.0	0.78					
LBP856 (340, -78)	16.8	24.4	7.6	0.31	0.15	257.6	RF Infill		22.0
and	70.1	94.5	24.4	0.23					
and	117.3	128.0	10.7	0.18					
and	134.1	160.0	25.9	0.18					
and	173.7	181.4	7.6	0.29					
and	192.0	207.3	15.2	0.34					
LBP857 (220, -52)	13.7	27.4	13.7	0.33	0.15	227.1	RF Infill		10.3
and	35.1	41.1	6.1	0.20					
and	111.3	120.4	9.1	0.28					
and	128.0	137.2	9.1	0.21					
LBP858 (210, -70)	88.4	94.5	6.1	0.21	0.15	294.1	RF Infill		21.1
and	146.3	208.8	62.5	0.32					
LBP859 (335, -70)	96.0	99.1	3.0	0.39	0.15	227.1	RF Infill		9.8
and	105.2	108.2	3.0	0.48					
and	132.6	138.7	6.1	0.22					
and	150.9	176.8	25.9	0.22					
LBP860 (350, -70)	39.6	59.4	19.8	0.21	0.15	213.4	RF Infill		15.9
and	88.4	96.0	7.6	0.19					
and	129.5	149.4	19.8	0.52					
including	129.5	131.1	1.5	1.14					
LBP861 (0, -90)	106.7	117.3	10.7	0.17	0.15	315.5	RF Geotech		48.5
and	120.4	155.4	35.1	0.72					
including	146.3	152.4	6.1	1.83	1.00				
and	172.2	175.3	3.0	0.36	0.15				
and	202.7	225.6	22.9	0.89					
including	207.3	219.5	12.2	1.36	1.00				
LBP862 (330, -58)	82.3	86.9	4.6	0.58	0.15	202.7	M Zone (813 Offset)		10.7
including	82.3	83.8	1.5	1.41					
and	144.8	147.8	3.0	0.34	0.15				
and	181.4	198.1	16.8	0.42					

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	Comments	g/t x m	
LBP863 (310, -45)	131.1	138.7	7.6	0.59	0.15	251.5	M Zone (813 Offset)		4.5	
including	131.1	132.6	1.5	1.05	1.00					
including	135.6	137.2	1.5	1.13						
LBP864 (290, -57)	103.6	125.0	21.3	2.13	0.15	221.0	M Zone (813 Offset)	Reduced AuCn Below 164	66.9	
including	109.7	114.3	4.6	8.67	1.00					
and including	109.7	112.8	3.0	12.23	5.00					
and	134.1	137.2	3.0	0.65	0.15					
and	164.6	173.7	9.1	1.65						
including	164.6	172.2	7.6	1.94	1.00					
and	178.3	192.0	13.7	0.32	0.15					
including	182.9	184.4	1.5	1.08	1.00					
LBP865 (130, -82)	No Significant Results					172.2	M Zone (813 Offset)			
LBP866 (30, -62)	70.1	80.8	10.7	0.68	0.15	202.7	M Zone (813 Offset)		9.3	
including	70.1	71.6	1.5	2.02	1.00					
and	150.9	155.4	4.6	0.44	0.15					
LBP867 (0, -90)	178.3	185.9	7.6	0.24	0.15	324.6	Rangefront Geotech		30.9	
and	214.9	221.0	6.1	0.26						
and	227.1	233.2	6.1	0.23						
and	239.3	283.5	44.2	0.34						
and	289.6	294.1	4.6	2.47						
LBP868 (300, -50)	No Significant Results					196.6	RF Infill			
LBP869 (350, -62)	88.4	93.0	4.6	0.24	0.15	419.1	RF Infill		32.8	
and	257.6	280.4	22.9	0.22						
and	281.9	295.7	13.7	0.35						
and	298.7	352.0	53.3	0.41						
LBP870 (330, -60)	13.7	19.8	6.1	0.32	0.15	336.8	RF Infill		37.6	
and	125.0	134.1	9.1	0.16						
and	135.6	155.4	19.8	0.25						
and	158.5	192.0	33.5	0.30						
and	221.0	234.7	13.7	0.18						
and	243.8	249.9	6.1	0.34						
and	289.6	303.3	13.7	0.47						
including	295.7	297.2	1.5	1.10						1.00
and	315.5	336.8	21.3	0.38	0.15					
LBP871 (285, -60)	16.8	21.3	4.6	0.40	0.15	251.5	RF Infill		30.1	
and	100.6	111.3	10.7	0.24						
and	123.4	134.1	10.7	0.24						
and	158.5	219.5	61.0	0.35						
and	227.1	234.7	7.6	0.20						
LBP872 (180, -45)	16.8	35.1	18.3	0.71	0.15	202.7	RF Infill		17.0	
including	16.8	22.9	6.1	1.45	1.00					
and	126.5	132.6	6.1	0.42	0.15					
and	149.4	155.4	6.1	0.25						
LBP873 (340, -70)	65.5	73.2	7.6	0.19	0.15	281.9	RF Infill		24.3	
and	83.8	93.0	9.1	0.22						
and	125.0	169.2	44.2	0.39						
including	150.9	152.4	1.5	1.03						1.00
and	192.0	205.7	13.7	0.26						0.15
LBP874 (70, -45)	0.0	12.2	12.2	0.25	0.15	172.2	RF Infill		6.4	
and	111.3	114.3	3.0	0.52						
and	161.5	170.7	9.1	0.20						